

EVEREST 4000

ISO 18752

RECOMMENDED FOR:

DEVELOPED TO WITHSTAND VERY DEMANDING CONDITIONS, VERY HIGH PERFORMANCE IN PRESSURE, PULSING AND FLEXING

RACCOMANDATO PER:


SVILUPPATO PER RESISTERE A CONDIZIONI MOLTO IMPEGNATIVE, PRESTAZIONI MOLTO ELEVATE IN PRESSIONE, IMPULSI E FLESSIONE



Features



Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
TSER406	10	3/8"	9,5	0.78	19,90	4000	280	16000	1120	2.56	65	0,38	0,57
TSER408	12	1/2"	12,8	0.90	23,00	4000	280	16000	1120	3,54	90	0,52	0,77
TSER410	16	5/8"	16,0	1.06	27,00	4000	280	16000	1120	3.94	100	0,63	0,97
TSER412	19	3/4"	19,0	1.18	30,10	4000	280	16000	1120	4,72	120	0,87	1,30
TSER416	25	1"	25,4	1,49	37,80	4000	280	16000	1120	5,90	150	1,19	1,77

	Everest 4000	3/4"	(19 mm)	ISO 18752 Flame Resistant MSHA IC-247	280 Bar 28,0 MPa	4000 Psi
---	---------------------	-------------	---------	--	---------------------	-----------------

MARKING/MARCATURA: TRANSFER TAPE

OPERATING

TEMPERATURE RANGE:

- 40°C/+120°C
(-40°F / +248°F)
with peaks of 125°C (257°F)

TUBE:

oil resistant synthetic rubber

REINFORCEMENT:

4 high tensile steel spirals

COVER:

special synthetic rubber

**TEMPERATURA
DI ESERCIZIO:**

- 40°C/+120°C
(-40°F / +248°F)
con punte di 125°C (257°F)

SOTTOSTRATO:

gomma sintetica resistente agli oli

RINFORZO:

4 spirali di acciaio ad alto carico

COPERTURA:

gomma sintetica speciale

TYPE APPROVAL:

