

TEKNO 2TE


EN 854 2TE - ISO 4079 -2TE

RECOMMENDED FOR:
 LOW PRESSURE LINES, RETURN LINES

RACCOMANDATO PER:
 LINEE DI BASSA PRESSIONE, LINEE DI RITORNO



Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
TH2TE03	5	3/16"	4,8	0,472	12,00	1160	80	4640	320	0,983	25	0,08	0,12
TH2TE04	6	1/4"	6,4	0,520	13,20	1088	75	4350	300	1,574	40	0,09	0,13
TH2TE05	8	5/16"	7,9	0,583	14,80	986	68	3944	272	1,967	50	0,11	0,17
TH2TE06	10	3/8"	9,5	0,646	16,40	914	63	3654	252	2,360	60	0,12	0,18
TH2TE08	12	1/2"	12,8	0,803	20,40	841	58	3364	232	2,754	70	0,17	0,26
TH2TE10	16	5/8"	16,0	0,961	24,40	725	50	2900	200	3,541	90	0,23	0,36
TH2TE12	19	3/4"	19,0	1,075	27,30	653	45	2610	180	4,327	110	0,26	0,40
TH2TE16	25	1"	25,4	1,362	34,60	580	40	2320	160	5,901	150	0,38	0,58
TH2TE20	31	1" 1/4	31,8	1,614	41,00	508	35	2030	140	6,688	170	0,47	0,72

	TEKNO 2TE	3/8"	(9,5mm)	EN 854 2TE ISO 4079-2TE	63 Bar 6,3 MPa	914 Psi
---	------------------	-------------	---------	----------------------------	-------------------	----------------

MARKING/MARCATURA: TRANSFER TAPE

OPERATING**TEMPERATURE RANGE:**

-40°C/+100°C
 (-40°F to +212°F)

TUBE:

oil resistant synthetic rubber

REINFORCEMENT:

1 high tensile textile braid

COVER:

weather resistant synthetic rubber.

TEMPERATURA**DI ESERCIZIO:**

-40°C/+100°C
 (-40°F to +212°F)

SOTTOSTRATO:

gomma sintetica resistente agli oli

RINFORZO:

1 treccia tessile ad alto carico

COPERTURA:

gomma sintetica resistente agli agenti atmosferici.