

VULCANAIR

RECOMMENDED FOR:
AIR COMPRESSOR SYSTEMS

RACCOMANDATO PER:
COMPRESSORI ARIA



Features:



Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
TH1SC04VA	6	1/4"	6,4	0.48	12.3	232	16	928	64	1.77	45	0,22	0,15
TH1SC06VA	10	3/8"	9,5	0.61	15.5	232	16	928	64	2.95	75	0,31	0,21
TH1SC08VA	12	1/2"	12,8	0.75	19.0	232	16	928	64	3.54	90	0,42	0,28
TH1SC10VA	16	5/8"	16	0.89	22.6	232	16	928	64	4.53	115	0,23	0,35
TH1SC12VA	19	3/4"	19	1.01	25.8	232	16	928	64	5.51	140	0,66	0,44
TH1SC16VA	25	1"	25,4	1.32	33.4	232	16	928	64	7.87	200	0,95	0,64
TH1SC20VA	31	1" 1/4	31,8	1.61	40.9	232	16	928	64	10.2	260	1,36	0,91
TH1SC24VA	38	1" 1/2	38,1	1.85	47.5	232	16	928	64	13.3	340	1,59	1,07
TH1SC32VA	51	2"	50,8	2.38	60.5	232	16	928	64	15.7	400	2,01	1,35


VulcanAIR 3/8"

(9,5mm)

175° C / 347° F

AIR COMPRESSOR

 16 Bar
1,6 MPa

232 Psi

MARKING/MARCATURA: TRANSFER TAPE

OPERATING
TEMPERATURE RANGE:

-20°C / +150°C (OIL)

-20°C / +175°C (AIR)

TUBE:

Black, smooth rubber lining

REINFORCEMENT:

1 high tensile wire braid

COVER:

Black syntetic rubber

**TEMPERATURA
DI ESERCIZIO:**

-20°C / +150°C (OLIO)

-20°C / +175°C (ARIA)

SOTTOSTRATO:

gomma nera liscia

RINFORZO:

1 treccia ad alto carico

COPERTURA:

Gomma nera sintetica